



Water, AFFF & FFFP Foam, Wet Chemical, CO₂ and Class D Fire Extinguishers + Vehicle Brackets



240X 252X 254 262 260



332X 322X 330X 331X



570 / 571

Type	Size (Capacity)	Model No.	Application	ULC/ULI Rating	F.M.	Shipping Wt. - Lbs.	Height (In.)	Width (In.)	Diam. (In.)	Initial Range (Ft.)	Discharge Time - Sec.	Temp. Range (Degrees F.)	U.S.C.G. Approved	Standard Bracket
WATER	2½ Gal.	240X	Hose & Nozzle	2A	Yes	7½	24½	9	7	45-55	50	+ 40 to +120 (Protect to - 40 w/ 506 Charge)	No	Wall
AFFF FOAM	6 Liter 2½ Gal.	254 250	Hose & Nozzle	2A:10B 3A:20B		8 11	18½ 24½	8 9	7	10-15	60-65	+ 40 to +120	No	Wall
FFFP FOAM	2½ Gal.	252X		3A:20B	Yes	11	24½	9						
WET CHEM. "Kitchen"	6 Liter 2½ Gal.	260 262	Hose & Wand	1B:C 2A:1B:C		12¾ 16¾	30 28	14	7	10-12	40 80	+ 40 to +120	No	Wall
CARBON DIOXIDE	5 Lbs.	322X	Horn	5B:C	Yes	14	17¾	8¼	5¼	3-8	10	- 40 to +120	Yes	Wall
	10 Lbs.	330X	Hose & Horn	5B:C	Yes	28¼	24	12	7	3-8	10	- 40 to +120	Yes	Wall
	15 Lbs.	331X	Hose & Horn	10B:C	Yes	37¾	30	12	7	3-8	12 1/2	- 40 to +120	Yes	Wall
	20 Lbs.	332X	Hose & Horn	10B:C	Yes	50¾	30	13	8	3-8	19	- 40 to +120	Yes	Wall
Class D (Sodium Chloride)	30 Lbs.	570	Hose & Applicator with Built in Nozzle	F.M. Listed (Tested to ANSI/UL1099 & 711)	Yes	53	27¾	16	7	3-6 (Applicator)	28	- 40 to +120	No	Wall
Class D (Copper)	30 Lbs.	571								8-10 (Nozzle)				

VEHICLE / MARINE (Single Strap) * AVIATION / HIGH VIBRATION (Two Strap)			HEAVY DUTY VEHICLE / MARINE STRAP TYPE			HEAVY DUTY VEHICLE / MARINE BOX TYPE			HEAVY DUTY VEHICLE RUBBER STRAP TYPE		
 817 818 * 817S * 818S 878			 821 808 846 861H			 807 809 810 811 812			 860 862 864		
MODEL	CYLINDER DIAMETER	APPLICABLE EXTG. MODEL	MODEL	CYLINDER DIAMETER	APPLICABLE EXTG. MODEL	MODEL	CYLINDER DIAMETER	APPLICABLE EXTG. MODEL	MODEL	CYLINDER DIAMETER	APPLICABLE EXTG. MODEL
845	2¾"	A620	821	4¼"	424X, A479, A500X	807	4¼"	424X, A479, A500X	860	3 - 4¼"	A403X, A417X
817	3"	A410, A417X				809	5"	322X, 441X, A456X, A457, A459X, 460	862	4¼ - 6¼"	322X, 424X, A459X, A479, A500X, 441X, A456X, A457, 460, 419X
878	3"	Universal 2 1/2 lb.	861H	4¼"	424X, A479, A500X	810	7"	240X, 252X, 254, 330X, 331X, 408X, 415, 423X, 621X, 652X, 570, 571	864	6½ - 8"	240X, 252X, 254, 260, 262, 330X, 331X, 332X, 408X, 415, 423X, 570, 571
* 817S	3"	A403X, A410, A417X	808	5"	A459X			332X			All 20 lb. Stored Pressure & Cartridge Operated Ext.
* 818S	4¼"	A479, A500X	846	5"	441X, 447X, A456X, A457, 460	811	8"	332X			
						812	6"	419X			

Note: Extinguisher are Coast Guard approved only with the bracket indicated on the nameplate (label). All brackets are compatible with old and new style ALUMINUM and BRASS valve extinguishers.